

Manhole Covers

BODY : MS/CS/SS

LINING : FEP/ PFA LINING THICKNESS: 3.5 to 4 MM
MINIMUM

SIZES AVAILABLE : 300 X 400, 350 X450, 500 NB FOR GLASS
LINED REACTOR

Glass-lined reactors can be damaged by frequent opening and closing of manways during the servicing of batch operations. Installing a manwaycover and protector ring maintains the corrosion resistance of the equipment while increasing the protection against mechanical damage. Now you can protect vulnerable manway components on glass-lined vessels by using the latest technological development in PTFE fabrications – the PTFE-lined manway cover. This thicker PTFE sheet much more durable than traditional 35 ml fluoropolymer sprayed coatings. Since it is bonded directly to the steel it will not slip, lift or curl.

Advantages

- Helps prevent glass damage if cover is dropped.
- Shorter pad-type nozzle allows wider viewing angle through sight glass.
- Complete interchangeability with other brands.
- Popular sizes stocked for fast delivery.

Specification

- Pressure from 150 psig to full vacuum
- Temperature up to 235 degree

Nominal Size	D	W	X	T
12X16	15	19	1	2-1/8
14X18	17	21	1	2-1/8
18 Round	21	21	1	2-1/8
20 Round DIN	24	24	1	-
24 Round	17-9/16	27-9/16	1	-

MAN HOLE COVERS

